

I CLAIM:

1. A transporter for a foldable tent comprising:
  - (a) a case which is open near a lower region; and
  - (b) at least one transport device releasably connected to the case at its lower region,the transport device comprising a horizontal plate which engages below the tent and supports the tent, and wherein the at least one transport device is releasably connected to the tent by way of a fastening means.
2. The transporter of claim 1, wherein the fastening means comprises a strip which releasably holds together at least a lower region of the tent and the transport device during transport.
3. The transporter of claim 1, wherein a vertical plate is connected to the horizontal plate, and is releasably connected to the tent by way of the fastening means.
4. The transporter of claim 1, wherein the tent comprises feet and tent rod assembly elements, and wherein the horizontal plate is arranged on the transport device in a manner such that, above the tent feet, the horizontal plate engages below the tent rod assembly elements.
5. The transporter of claim 4, wherein the horizontal plate engages so far below the tent that it engages below corner posts of the tent and below tent rod assembly components on one side of the tent.
6. The transporter of claim 1, wherein the transporter comprises a wheel on each of two opposite sides, the wheels being releasably connected to the transport device via a hub, and comprising a ring which rotates over the hub.
7. The transporter of claim 1, wherein the case may be closed along one longitudinal side by way of a zipper.
8. The transporter of claim 1, wherein the case may be closed along one longitudinal side by way of a Velcro strip.

9. The transporter of claim 1, wherein the case is provided with at least one hand-grip near the upper region.

10. The transporter of claim 6, wherein when not in use, the wheels are stored in a chamber near the top of the case, the chamber being provided with a cover.

11. The transporter of claim 6, wherein the transporter comprises at least two transport devices and at least four wheels for displacement in the upright position.